

# TECHNICAL DATA SHEET

## GENERAL INFORMATION

- Product Name : Panax Eco Green 500L
- Chemical Type : The mixture of Phthalocyanine Green and Extender
- Main Application : Paint
- Pigment No. : Not listed

Full Shade



Tinting Shade (1:25)



## DESCRIPTIONS

Non-toxic pigment, Good Light Fastness, Good Heat Resistance

## PHYSICAL PROPERTIES

- Specific Gravity : 3.5
- Moisture Content : Max 1.0 %
- PH(Kneader extract) : 5~7
- Dispersion( $\mu\text{m}$ ) : Max 40 (Aprecision gage) by Hoover Muller (50\*2)
- Hardness : Soft

## RESISTANCE DATA

- |                               |           |                 |          |
|-------------------------------|-----------|-----------------|----------|
| • Light Fastness (Full Shade) | : 5 (1-5) | Acid(5% HCl)    | : 4(1-5) |
| • Light (Tint Shade)          | : 4 (1-5) | Alkali(5% NaOH) | : 4(1-5) |
| • Heat (210°C×10min)          | : 3 (1-5) | M.E.K           | : 4(1-5) |
| • Water                       | : 4 (1-5) |                 |          |



## UKSEUNG CHEMICAL CO., LTD

HEAD OFFICE : # 174, Gaejwa-ro, Geumjeong-gu, Busan, South Korea  
TEL. 051) 718-5345 ~ 8 / FAX. 051) 529-7272